

# Double Wall Tanks


Double wall tanks (IMT) provide the best protection against hazardous chemical spills into the environment. Inner tank dome overlaps outer tank sidewall to prevent rainwater, snow and debris from entering into the containment basin. Our ability to heat trace and insulate make these tanks perfect for temperature sensitive chemicals. Molded-in lifting lugs and upper fitting flats are standard. Molded-in lower fitting flats, along with a sturdy Assmann designed bottom outlet, reduce the cost of expensive double wall outlets.

All double wall tanks are designed with wall thicknesses equal to or greater than that required by ASTM D-1998 standards. Double wall tanks can be customized by adding Seismic zone 4 or 120 MPH wind load tie down assemblies, leak detection, ultrasonic level indicators, and ladders.

## Accessories for Double Wall Tanks

- Seismic zone 4 restraint
- 120 MPH wind load restraint
- Ultrasonic level indicator
- Leak detection system
- High and low level alarms
- Heat tracing and insulation
- Fiber Reinforced Ladders
- Top discharge assemblies with foot valve
- Standard 16" or optional 21" top manways

Double wall tanks can be equipped with accessories to fit your specifications (See pages 13-21.)



Model Number	Cap. (US Gals)	Dimensions (inches)		Weight (lbs) Linear Polyethylene						Weight (lbs) Crosslink Polyethylene						Access Open. (in)
				Primary Sp. Gravity			Secondary Sp. Gravity			Primary Sp. Gravity			Secondary Sp. Gravity			
		Dia.	Hgt.	1.5	1.9	2.2	1.5	1.9	2.2	1.5	1.9	2.2	1.5	1.9	2.2	
<b>IMT 550</b>	550	60	73	N/A	130	159	N/A	130	151	N/A	130	159	N/A	130	159	16
<b>IMT 1050</b>	1050	72	87	185	205	233	191	244	283	185	205	226	176	221	256	16
<b>IMT 1550</b>	1550	72	123	325	408	472	309	392	454	297	380	440	283	359	416	16
<b>IMT 2050</b>	2050	72	159	551	691	809	596	748	875	505	633	738	545	697	799	16
<b>IMT 2550</b>	2550	96	119	643	823	953	499	632	732	600	748	866	457	579	671	16
<b>IMT 3050</b>	3050	96	138	817	1022	1183	694	879	1018	739	944	1093	636	806	933	16
<b>IMT 4050</b>	4050	96	177	1252	1607	1870	1178	1492	1728	1158	1476	1700	1178	1492	1728	16
<b>IMT 5250</b>	5250	119	154	1484	1920	2225	1342	1699	1968	1372	1753	2025	1230	1558	1804	16
<b>IMT 6550</b>	6550	119	186	2181	2778	3200	2028	2569	2974	2000	2570	2960	2028	2569	2974	16

Model number availability and individual specifications subject to change without notice. Gallonage and weights are approximate. All wall thicknesses conform to ASTM D-1998.



Phone: 888-357-3181 • Fax: 888-Tank Fax (826-5329)  
 Phone: 260-357-3181 • Fax: 260-357-3738  
 E-mail: [info@assmann-usa.com](mailto:info@assmann-usa.com) • [www.assmann-usa.com](http://www.assmann-usa.com)